

Single-ended I/O Cordsets-M8 (Angled-male)

Description:

Used for sensors, I/O connector connecting. Standard M8(angled-male) threaded connection.
3, 4-core are optional. Customized cable lengths. Degree of protection IP67.

Features:

- PVC and PUR cable are optional
- A-coded interface
- Optional LED indicator

* All technical information about the raw cable for connectors, please refer to the "cable" section (P513).



Type Code

Cable jacket	Description	Type	Pin	Rated current/voltage	Cable length	Wire section
PVC	Male 3-core	CB8.3-2	3	4A/60V	2m	0.25mm ²
	Male 4-core	CB8.4-2	4	4A/30V	2m	0.25mm ²
PUR	Male 3-core	CB8.3-2/P	3	4A/60V	2m	0.25mm ²
	Male 4-core	CB8.4-2/P	4	4A/30V	2m	0.25mm ²
PVC Shielded	Male 3-core	CB8.3-2/WS	3	4A/60V	2m	0.25mm ²
	Male 4-core	CB8.4-2/WS	4	4A/30V	2m	0.25mm ²
PUR Shielded	Male 3-core	CB8.3-2/WS/P	3	4A/60V	2m	0.25mm ²
	Male 4-core	CB8.4-2/WS/P	4	4A/30V	2m	0.25mm ²

Selection Instructions

CB8.3 - 2/P
① ②

Attn : ①: Customized cable lengths are available.
②: Cable jacket or function can be customized according to the requirements.

Additional Information

Cable Length

